

Safety Data Sheet

hydro destainer

01

Chemical Product and Company Identification Product Name Product Use Product Code Hydro Destainer Laundry Detergent

3868

Call 'Chemtrec' 1-800-424-9300

Santec Inc.

1420 East Linden Avenue, Linden NJ 07036

02

Hazards
Identification

Emergency Overview

For Medical Emergency

Supplier's Information

Signal Word: Danger

Hazarad Statement: Risk of serious damage to eyes. Harmful if swallowed.

Acute Effects

Eyes: May cause severe eye irritation. Potential risk of serious damage to eyes.

Skin: Prolonged skin contact may cause skin irritation.

Inhalation: Inhalation of dust may cause irritation to gastro intestinal or respiratory tract.

Ingestion: Harmful if swallowed. May cause burns to mouth, throat and stomach.

Chronic Effects

Carcinogenicity: No known critical effets or citical hazards.

Product /Ingredient Name: Not available.

03

Composition/ Information on Ingredients Name of Hazardous Ingredients

Sodium Percarbonate

CAS No. 15630-89-4

WT.% 50-100

Page: 1 of 3

1

*Hazard Determination

System (HDS):

Flammability

Health

Reactivity

04

First Aid Measures **Eye Contact:** Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the uppper and lower eyelids. Get medical attention immediately.

Skin Contact: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Get medical attention if irritation persists.

Inhalation: Move exposed person to fresh air. Flush mouth and nasal passages with water repeatedly. Get medical attention if symptoms persist.

Ingestion: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If affected person is conscious, give plenty of water to drink. Get medical attention immediately.

05

Fire Fighting Measures Suitable Fire Extinguishing Media: Use water spray, fog or foam

Specific Hazards Arising from the Chemical: None

Hazardous Thermal Decomposition Products: Carbon oxides (CO, CO₂), oxygen.

Specific Fire-Fighting Methods: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. **Specific Protective Equipment for Fire-Fighters:** Fire-Fighters should wear appropriate protective equipment and self contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

• •

Accidental Release Measures **Spill Clean Up:** Move containers from spill area. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimum hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.



Safety Data Sheet

hydro destainer

Page: 2 of 3

07

Handling and Storage

Handling: Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Avoid breathing dust. Do not ingest. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reuse container. Wash thoroughly after handling.

Storage: Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Contains moisture-sensitive material. Store in a dry place. Do not store in unlabeled containers. Keep out of the reach of children.

08

Exposure Controls/ Personal Protection

Ingredient Name Exposure Limits

Sodium Percarbonate OSHA PEL TWA 5 mg/m³, Form: Dust

Personal Protective Equipment (PPE)

Eyes: Safety glasses, splash goggles.

Skin: Wear appropriate protective clothing to prevent skin contact. Wear apron or overall if there is a risk of exposure to spills.

Body: For prolonged or repeated handling, use gloves. Nitrile gloves. Rubber gloves. Neoprene gloves.

Respiratory: If dust is generated and ventilation is inadequate, use respirator that will protect against dust/mist.

Physical and Chemical Properties

Physical State Granular Powder

Color White Odor None

pH 10.4-10.6 (1% solution)

Flash point None **Explosion limits** Not available Flammability (solid, gas) Not available **Melting point** Not available **Boiling point** Not available Not available Evaporation rate (butyl acetate = 1) Not available Vapor pressure Vapor density Not available 67 lb./ft3 **Relative density**

Solubility Easily soluble in the following materials: cold water and hot water

Partition coefficient n-octano/waterNot availableAuto-ignition temperatureNot availableDecompostion temperatureNot availableOdor thresholdNot available

10

Stability and Reactivity

Stability: The product is stable.

Possibilty of hazardous reactions: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid: Exposure to moisture, overheat.

Materials to avoid: Strong acids, flammable material, combustiable material, reducing agents.

Hazardous decomposition products: Carbon oxides (CO, CO₂), oxygen.



Safety Data Sheet hydro destainer

Page: 3 of 3

11	Toxicological Information	Product /Ingredient Name Sodium Percarbonate	Result LD50 Oral	Species Rat	Dose 1134 mg/kg				
12	Ecological Information	N/A							
13	Disposal Considerations Waste Information Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.								
14	Transport Information	Regulatory Information	UN Number	Proper Ship	oper Shipping Name		PG*	Label	
		DOT Classification		oxidizing solic carbonate per	5.1	III			
	Note: DOT classification applies to most package sizes. For specific container size classifications or size exceptions, refer to the bill of lading with your shipment. PG*: Packing Group								
15	Regulatory Information								
		SARA 313 Form R-Reporting requirements	Product name No listed substar		number	Concentration			
16	Ecological Information	To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.							
	Date of Issue: 12/30/2014								