

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 03/06/2012

Reviewed on 03/06/2012

* 1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name: Esdogen Bleach**
- **Application of the substance / the preparation**
Activated concentrate for oxygen bleaching for textiles made of cotton and synthetics. For use in the ESDOGEN system.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
- **Manufacturer:**
Chemische Fabrik Kreussler & Co. GmbH
Postfach 120454
D-65082 Wiesbaden
- **Supplier:**
Kreussler Inc., 6103 Johns Road Suit 7, Tampa, FL 33634,
Phone 813-884-1499, Fax 813-884-1599,
Internet: www.kreussler.com, e-mail: office-tampa@kreussler.com
- **Information department:**
Abteilung TQM
Herr Vogel
+49 (0) 611 9271-175
Kurt.Vogel@kreussler.com
- **Emergency telephone number:** +49 (0) 611 9271-0

* 2 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
7722-84-1	hydrogen peroxide solution	C R34; Xn R20/22; O R8	30-50%
64-19-7	acetic acid	C R35 R10	1.0-5.0%
79-21-0	peracetic acid	C R35; Xn R20/21/22; O R7; N R50 R10	1.0-5.0%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**
Corrosive
Causes burns.
.....
Harmful
Harmful by inhalation and if swallowed.
.....
Oxidizing
Contact with combustible material may cause fire.
- **Information concerning particular hazards for human and environment:**
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
- **Classification system:**
The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.
- **Label elements**
- **Labelling according to EU guidelines:**
The product has been classified and marked in accordance with directives on hazardous materials.

(Contd. on page 2)

— USA —

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 03/06/2012

Reviewed on 03/06/2012

Trade name: Esdogen Bleach

(Contd. of page 1)

· **Code letter and hazard designation of product:**



C Corrosive
O Oxidizing

· **Hazard-determining components of labelling:**

hydrogen peroxide solution
peracetic acid

· **Risk phrases:**

Contact with combustible material may cause fire.
Harmful by inhalation and if swallowed.
Causes burns.

· **Safety phrases:**

Keep container tightly closed in a cool place.
Keep away from alkaline solutions.
Keep away from flammable organic substances.
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
After contact with skin, wash immediately with plenty of soap and water.
Wear suitable protective clothing, gloves and eye/face protection.
In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 3
Fire = 3
Reactivity = 0

The substance possesses oxidizing properties.

· **HMIS-ratings (scale 0 - 4)**



Health = 3
Fire = 3
Reactivity = 0

4 First aid measures

- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact:**
Call a doctor immediately.
Rinse opened eye for several minutes under running water.
- **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Danger** Danger of gastric perforation.

5 Firefighting measures

- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:**
organic compounds
Water with full jet

(Contd. on page 3)

— USA —

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 03/06/2012

Reviewed on 03/06/2012

Trade name: **Esdogen Bleach**

(Contd. of page 2)

- **Special hazards arising from the substance or mixture**

If involved in fire, may decompose yielding oxygen.

Risk of overpressure and burst due to decomposition in confined spaces and pipes.

Release of oxygen may support combustion.

In case of fire, remove the endangered containers and bring to a safe place, if this can be done safely. Keep away from heat.

If necessary:

In case of fire cool the containers that are at risk with water or dilute with water (flooding).

- **Protective equipment:** Wear fully protective suit.

- **Additional information**

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Product does not burn

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:**

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- **Handling:**

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.

- **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

Oxidizing anorganic peroxygene compound.

Contact with inflammable materials can cause ignition.

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Provide acid-resistant floor.

Suitable material for receptacles and pipes: steel or stainless steel.

Unsuitable material for receptacle: aluminium.

- **Information about storage in one common storage facility:**

Store away from reducing agents.

Do not store together with alkalis (caustic solutions).

Do not store together with metal salts.

- **Further information about storage conditions:**

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

Do not gas tight seal receptacle.

- **Specific end use(s)** No further relevant information available.

* 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 4)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 03/06/2012

Reviewed on 03/06/2012

Trade name: Esdogen Bleach

(Contd. of page 3)

· Components with limit values that require monitoring at the workplace:

7722-84-1 hydrogen peroxide solution (30-50%)

PEL	1.4 mg/m ³ , 1 ppm
REL	1.4 mg/m ³ , 1 ppm
TLV	1.4 mg/m ³ , 1 ppm

64-19-7 acetic acid (1.0-5.0%)

PEL	25 mg/m ³ , 10 ppm
REL	Short-term value: 37 mg/m ³ , 15 ppm Long-term value: 25 mg/m ³ , 10 ppm
TLV	Short-term value: 37 mg/m ³ , 15 ppm Long-term value: 25 mg/m ³ , 10 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

Do not eat, drink, smoke or sniff while working.

Ensure that washing facilities are available at the work place.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Filter ABEK-P2

· **Protection of hands:**



Protective gloves

· **Material of gloves**

PVC or PE gloves

Recommended thickness of the material: ≥ 0.4 mm

· **Not suitable are gloves made of the following materials:**

Leather gloves

Strong gloves

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **General Information**

· **Appearance:**

Form:	Fluid
Color:	Colorless
Odor:	Pungent

· **pH-value at 20°C (68 °F):** 1

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Undetermined.

(Contd. on page 5)

— USA —

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 03/06/2012

Reviewed on 03/06/2012

Trade name: Esdogen Bleach

(Contd. of page 4)

· Flash point:	Not applicable.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Vapor pressure at 20°C (68 °F):	23 hPa (17 mm Hg)
· Density at 20°C (68 °F):	1.09 g/cm ³ (9.096 lbs/gal)
· Solubility in / Miscibility with Water:	Fully miscible.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** To avoid thermal decomposition do not overheat.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Corrosive gases/vapors

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

79-21-0 peracetic acid

Oral	LD-50	314 mg/kg (rat)
Dermal	LD-50	1912 mg/kg (rabbit)
Inhalative	LC-50/4 h	0.49 mg/l (rat)

- **Primary irritant effect:**

- **on the skin:** Caustic effect on skin and mucous membranes.
- **on the eye:** Strong caustic effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Corrosive

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

12 Ecological information

- **Aquatic toxicity:**

79-21-0 peracetic acid

EC-50 3 h	5.1 mg/l (Belebtschlamm)
EC-50 48h	0.5-1.1 mg/l (Daphnia magna)
IC-50 120h	0.18 mg/l (Selenastrum capricomutum) (US-EPA-Methode)
LC-50 96h	1-2 mg/l (Oncorhynchus mykiss)
	11 mg/l (Pleuronectes platessa)
NOEC 21,0 d	0.05 mg/l (Daphnia magna) (OECD 211)

(Contd. on page 6)

— USA —

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 03/06/2012

Reviewed on 03/06/2012

Trade name: Esdogen Bleach

(Contd. of page 5)

- **Persistence and degradability** No further relevant information available.
- **Other information:** abiotic degradation through hydrolysis and reduction.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
The product may not be released into the environment without control.
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Dispose of in accordance with local, state, and federal Regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

* 14 Transport information

· UN-Number	
· DOT, ADR, IMDG, IATA	UN3149
· UN proper shipping name	
· DOT, IMDG, IATA	HYDROGEN PEROXIDE AND PEROXYACETIC ACID MIXTURE, STABILIZED
· ADR	3149 HYDROGEN PEROXIDE AND PEROXYACETIC ACID MIXTURE, STABILIZED
· Transport hazard class(es)	
· DOT, IMDG, IATA	
· Class	5.1 Oxidising substances.
· Label	5.1+8
· ADR	
· Class	5.1 Oxidizing substances
· Label	5.1+8
· Packing group	
· DOT, ADR, IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Oxidizing substances
· Danger code (Kemler):	58
· EMS Number:	F-H,S-Q
· Segregation groups	Peroxides
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.

15 Regulatory information

· Sara

· Section 355 (extremely hazardous substances):	
7722-84-1	hydrogen peroxide solution
79-21-0	peracetic acid

(Contd. on page 7)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 03/06/2012

Reviewed on 03/06/2012

Trade name: **Esdogen Bleach**

(Contd. of page 6)

· Section 313 (Specific toxic chemical listings):		
79-21-0	peracetic acid	
· TSCA (Toxic Substances Control Act):		
All ingredients are listed.		
· Proposition 65		
· Chemicals known to cause cancer:		
None of the ingredients is listed.		
· Chemicals known to cause reproductive toxicity for females:		
None of the ingredients is listed.		
· Chemicals known to cause reproductive toxicity for males:		
None of the ingredients is listed.		
· Chemicals known to cause developmental toxicity:		
None of the ingredients is listed.		
· Carcinogen categories		
· EPA (Environmental Protection Agency)		
None of the ingredients is listed.		
· IARC (International Agency for Research on Cancer)		
7722-84-1	hydrogen peroxide solution	3
· NTP (National Toxicology Program)		
None of the ingredients is listed.		
· TLV (Threshold Limit Value established by ACGIH)		
7722-84-1	hydrogen peroxide solution	A3
· MAK (German Maximum Workplace Concentration)		
7722-84-1	hydrogen peroxide solution	4
79-21-0	peracetic acid	3B
· NIOSH-Ca (National Institute for Occupational Safety and Health)		
None of the ingredients is listed.		
· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		
· Canadian Substances Listings:		
· Canadian Domestic Substances List (DSL):		
7722-84-1	hydrogen peroxide solution	
64-19-7	acetic acid	
79-21-0	peracetic acid	
· Canadian Ingredient disclosure list (limit 0.1%)		
All ingredients are listed.		
· Canadian Ingredient disclosure list (limit 1%)		
7722-84-1	hydrogen peroxide solution	
64-19-7	acetic acid	
79-21-0	peracetic acid	

· **Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

· **Hazard symbols:**

C Corrosive
O Oxidizing

(Contd. on page 8)

— USA —

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 03/06/2012

Reviewed on 03/06/2012

Trade name: Esdogen Bleach

(Contd. of page 7)

· Hazard-determining components of labelling:

hydrogen peroxide solution
peracetic acid

· Risk phrases:

Contact with combustible material may cause fire.
Harmful by inhalation and if swallowed.
Causes burns.

· Safety phrases:

Keep container tightly closed in a cool place.
Keep away from alkaline solutions.
Keep away from flammable organic substances.
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
After contact with skin, wash immediately with plenty of soap and water.
Wear suitable protective clothing, gloves and eye/face protection.
In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The information of Items 4 through 8 and 10 through 12 partially refers not to the use and the proper application of the product (see Directions for Use/Product Information) but to the release of larger quantities in the case of accidents and irregularities.

The information exclusively describes the safety requirements of the product(s) and is based on the present state of our experience.

Non-ionic tensides can have varying characteristics and classifications despite same CAS-No.

· Department issuing MSDS:

Abteilung TQM
Herr Vogel
+49 (0) 611/9271-175

· Contact: Herr Vogel**· * Data compared to the previous version altered.**

USA
