santec [®]		Safety Data Sheet surge builder			Page: 1 of 3	
01	Chemical Product and Company Identification	Product Name Product Use Product Code For Medical Emergency Supplier's Information	Surge Builder Alkalinity Booster 3006 Call 'Chemtrec' 1-800-424-9 Santec Inc. 1420 East Linden Avenue, Lir			
02	Hazards Identification	Emergency Overview Signal Word: Danger Hazarad Statement: Causes seve		Sys	zard Determination tem (HDS):	
		Acute Effects Eyes: Severely corrosive to the eyes injury (blindness). Skin: Severely corrosive to the skin. contact. Skin inflammation is charace Inhalation: May give off gas, vapor the spray or mist may produce sever of breath. Ingestion: Toxic if swallowed. May of <u>Chronic Effects</u> Carcinogenicity: No known critical Product /Ingredient Name: Not a	Causes severe burns. The amounterized by itching, scaling, redde or dust that is very irritating or correct irritation of respiratory tract, ch cause burns to mouth, throat and l effets or citical hazards.	osure may cause sever unt of tissue damage de ning or, occasionally, b prrosive to the respirato aracterized by coughin	epends on length of listering. ory system. Inhalation of g, choking or shortness	
03	Composition/ Information on Ingredients	Name of Hazardous Ingredient Sodium Hydroxide Tetra Sodium Ethylenediamine Tetra	1310-73-2	WT.% 15-25 1-2		
04	First Aid Measures	Eye Contact: Check for and remove for 15 minutes. Seek medical attenti Skin Contact: Wash skin with copi Inhalation: Remove to fresh air. See Ingestion: Do not induce vomiting.	on immediately. ous amounts of water. Seek mee ek medical attention immediately	lical attention immediat	ely.	
05	Fire Fighting Measures	Suitable Fire Extinguishing Mer Specific Hazards Arising from t container may burst. Hazardous Thermal Decomposi Carbon Dioxides, Carbon Monoxide Specific Fire-Fighting Methods the incident if there is a fire. No act Specific Protective Equipement equipment and self contained br pressure mode.	he Chemical: In a fire or if hea ition Products: Decomposition es. s: Promptly isolate the scene b ion shall be taken involving any t for Fire-Fighters: Fire-Fighte	ted, a pressure increase n products may include y removing all persons personal risk or withou ers should wear approp	e following materials; s from the vicinity of ut suitable training. priate protective	
06	Accidental Release Measures	Spill Clean Up: Put on appropriat Move Containers from spill area. Dilu and place in an appropriate waste di	ite with water and mop up if wate	er-soluble or absorb wit	h an inert dry material	

*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimum hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.

santec		Safety Data Sheet surge builder	Page: 2 of				
07	Handling and Storage	 Handling: Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin clothing. Do not breathe vapor or mist. Do not ingest. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reuse container. Wash thorough after handling. Storage: Store between the following temperatures: 4.44 to 48.9°C (40 to 120°F). Store in accordance wit local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated ar away from incompatible materials (see section 10) and food and drink. Separate from acids. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed ar kept upright to prevent leakage. Do not store in unlabeled containers. 					
08	Exposure Controls/ Personal Protection		osure Limits IA PEL 2 mg/m³				
		Personal Protective Equipment (PPE					
		 Skin: Use synthetic apron, other protective equipment as necessary to prevent skin contact. Body: Face shield, full suit, vapor respirator, boots and gloves. Respiratory: A self contained breathing apparatus should be used to avoid inhalation of product. Be sure to use an approved /certified respirator or equivalent. 					
09	Physical and	Physical State	Clear liquid				
09	Chemical	Physical State Color	Clear liquid Tan				
09							
09	Chemical	Color	Tan				
09	Chemical	Color Odor	Tan Bland				
09	Chemical	Color Odor pH	Tan Bland ≥ 13				
09	Chemical	Color Odor pH Flash point Explosion limits Flammability (solid, gas)	Tan Bland ≥ 13 None				
09	Chemical	Color Odor pH Flash point Explosion limits Flammability (solid, gas) Melting point	Tan Bland ≥ 13 None Not available Not available Not available				
09	Chemical	Color Odor pH Flash point Explosion limits Flammability (solid, gas) Melting point Boiling point	Tan Bland ≥ 13 None Not available Not available Not available >100°C (212F)				
09	Chemical	Color Odor pH Flash point Explosion limits Flammability (solid, gas) Melting point Boiling point Evaporation rate (butyl acetate = 1)	Tan Bland ≥ 13 None Not available Not available >100°C (212F) Not available				
09	Chemical	Color Odor pH Flash point Explosion limits Flammability (solid, gas) Melting point Boiling point Evaporation rate (butyl acetate = 1) Vapor pressure	Tan Bland ≥ 13 None Not available Not available >100°C (212F) Not available Not available Not available				
09	Chemical	Color Odor pH Flash point Explosion limits Flammability (solid, gas) Melting point Boiling point Evaporation rate (butyl acetate = 1) Vapor pressure Vapor density	Tan Bland ≥ 13 None Not available Not available >100°C (212F) Not available Not available Not available Not available				
09	Chemical	Color Odor pH Flash point Explosion limits Flammability (solid, gas) Melting point Boiling point Evaporation rate (butyl acetate = 1) Vapor pressure Vapor density Relative density	Tan Bland \geq 13 None Not available Not available >100°C (212F) Not available Not available Not available Not available Not available 1.26 (Water = 1)	vater and hot water			
09	Chemical	Color Odor pH Flash point Explosion limits Flammability (solid, gas) Melting point Boiling point Evaporation rate (butyl acetate = 1) Vapor pressure Vapor density Relative density Solubility	Tan Bland \geq 13 None Not available Not available >100°C (212F) Not available Not available Not available Not available 1.26 (Water = 1) Easily soluble in the following materials: cold w	vater and hot water			
09	Chemical	Color Odor pH Flash point Explosion limits Flammability (solid, gas) Melting point Boiling point Evaporation rate (butyl acetate = 1) Vapor pressure Vapor density Relative density Solubility Partition coefficient n-octano/water	Tan Bland \geq 13 None Not available Not available >100°C (212F) Not available Not available Not available Not available 1.26 (Water = 1) Easily soluble in the following materials: cold w Not available	vater and hot water			
09	Chemical	Color Odor pH Flash point Explosion limits Flammability (solid, gas) Melting point Boiling point Evaporation rate (butyl acetate = 1) Vapor pressure Vapor density Relative density Solubility Partition coefficient n-octano/water Auto-ignition temperature	Tan Bland \geq 13 None Not available Not available >100°C (212F) Not available Not available Not available Not available 1.26 (Water = 1) Easily soluble in the following materials: cold w	vater and hot water			
09	Chemical	Color Odor pH Flash point Explosion limits Flammability (solid, gas) Melting point Boiling point Evaporation rate (butyl acetate = 1) Vapor pressure Vapor density Relative density Solubility Partition coefficient n-octano/water	Tan Bland \geq 13 None Not available Not available >100°C (212F) Not available Not available Not available 1.26 (Water = 1) Easily soluble in the following materials: cold w Not available Not available				
09	Chemical	Color Odor pH Flash point Explosion limits Flammability (solid, gas) Melting point Boiling point Evaporation rate (butyl acetate = 1) Vapor pressure Vapor density Relative density Solubility Partition coefficient n-octano/water Auto-ignition temperature Decompostion temperature	Tan Bland \geq 13 None Not available Not available >100°C (212F) Not available Not available Not available 1.26 (Water = 1) Easily soluble in the following materials: cold w Not available Not available Not available Not available Not available Not available Not available Not available				
09	Chemical	Color Odor pH Flash point Explosion limits Flammability (solid, gas) Melting point Boiling point Evaporation rate (butyl acetate = 1) Vapor pressure Vapor density Relative density Solubility Partition coefficient n-octano/water Auto-ignition temperature Decompostion temperature Odor threshold Viscosity Stability: The product is stable.	Tan Bland \geq 13 None Not available Not available >100°C (212F) Not available Not available Not available 1.26 (Water = 1) Easily soluble in the following materials: cold w Not available Not available)			
09	Chemical Properties	Color Odor pH Flash point Explosion limits Flammability (solid, gas) Melting point Boiling point Evaporation rate (butyl acetate = 1) Vapor pressure Vapor density Relative density Solubility Partition coefficient n-octano/water Auto-ignition temperature Decompostion temperature Odor threshold Viscosity Stability: The product is stable. Possibilty of hazardous reactions: U	Tan Bland \geq 13 None Not available Not available >100°C (212F) Not available Not available Not available 1.26 (Water = 1) Easily soluble in the following materials: cold w Not available Not available)			
09	Chemical Properties Stability and	Color Odor pH Flash point Explosion limits Flammability (solid, gas) Melting point Boiling point Evaporation rate (butyl acetate = 1) Vapor pressure Vapor density Relative density Solubility Partition coefficient n-octano/water Auto-ignition temperature Decompostion temperature Odor threshold Viscosity Stability: The product is stable. Possibilty of hazardous reactions: U occur.	Tan Bland \geq 13 None Not available Not available >100°C (212F) Not available Not available Not available 1.26 (Water = 1) Easily soluble in the following materials: cold w Not available Not available)			
09	Chemical Properties	Color Odor pH Flash point Explosion limits Flammability (solid, gas) Melting point Boiling point Evaporation rate (butyl acetate = 1) Vapor pressure Vapor density Relative density Solubility Partition coefficient n-octano/water Auto-ignition temperature Decompostion temperature Odor threshold Viscosity Stability: The product is stable. Possibilty of hazardous reactions: U occur. Conditions to avoid: Strong acids.	Tan Bland \geq 13 None Not available Not available >100°C (212F) Not available Not available Not available 1.26 (Water = 1) Easily soluble in the following materials: cold w Not available Not available)			



11	Toxicological Information	Product /Ingredient Name Sodium Hydroxide Tetra Sodium Ethylenediamine Te	LD	esult 950 Oral 950 Oral	Species Rat Rat	Dose 500 mg/kg 3050 mg/kg		
12	Ecological Information	N/A						
13	Disposal Considerations	Waste Information Waste must be disposed of in a Consult your local or regional au				vironmental con	trol regu	lations.
14	Transport	Regulatory Information	UN Number	Proper S	Shipping Nan	ne Classes	PG*	Labe
	mation	DOT Classification	UN3266	inorganic	e liquid, basic, ;, n.o.s. hydroxide)	8	III	
		Note: DOT classification applies exceptions, refer to the bill of ladi PG*: Packing Group			cific container s	ize classification:	s or size	
15	Regulatory Information	U.S. Federal Regulations TSCA 8(b) inventory: All comp SARA 302/304/311/312 extra SARA 302/304 emergency p	emely hazardou	s substance	es: No listed su			
		SARA 313 Form R-Reporting requirements	Product na No listed sub		CAS number	Con	centrati	<u>on</u>
16	Ecological Information	To the best of our knowledge, the supplier nor any of its subsidiar information contained herein.		liability what	soever for the	accuracy of cor	npletene	ss of the