

SAFETY DATA SHEET

SECTION 1 — PRODUCT IDENTIFICATION

HLR LABEL & ADHESIVE REMOVER **Product identifier:**

Product Number: 1021

Intended Use: Removal of heat applied labels & adhesives from textiles.

Manufacturer's name and address: Refer to supplier

Supplier name and address:

ALBATROSS USA INC./EXPERT WORLDWIDE

36-41 36th Street 5439 San Fernando Road West

Long Island City, New York Los Angeles, California **United States United States**

90039 11106

718-392-6272 818-543-5850

Emergency Telephone #: Chemtrec (Day or Night) 800-424-9300

(For Chemical Emergency: Spill, Leak, Fire, Exposure or Accident)

This MSDS complies with 29CFR 19190.1200 (Hazard Communication Standard) and WHMIS regulations.

IMPORTANT: Read this MSDS before handling and disposing of this product. Pass this information on to employees, customer, and users of this product.

SECTION 2 — HAZARDS IDENTIFICATION

Flammable Liquids, Category 2 Eye Irritation, Category 2A

Specific Target Organ Toxicity, Category 3





GHS Signal Word: Danger

GHS Hazard Phrases: H225: Highly flammable liquid and vapour

> H319: Causes serious eye irritation H335: May cause respiratory irritation. H336: May cause drowsiness or dizziness.

GHS Precaution Phrases: P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking

P233: Keep container tightly closed

P240: Ground/bond container and receiving equipment

P241: Use explosion-proof electrical/ventilating/lighting equipment

P242: Use only non-sparking tools

P243: Take precautionary measures against static discharge

P264: Wash hands thoroughly after handling

P280: Wear protective gloves/protective clothing/eye protection/face protection

HLR Label & Adhesive Remover Page 2 of 9

P261: Avoid breathing gas/mist/vapors/spray

P271: Use only outdoors or in a well-ventilated area

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P337+313: If eye irritation persists, get medical advice/attention.

P312: Call a POISON CENTER or doctor/physician if you feel unwell.

P370+378: In case of fire, use dry chemical to extinguish

P403+233: Store in well-ventilated place. Keep container tightly closed.

P405: Store locked up

P501: Dispose of contents/container according to local, state and federal regulations

Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3 — COMPOSITION/INFORMATION ON INGREDIENTS

Substances:

Chemical name:	Concentration	CAS Number	
Methyl Acetate	>80%	79-20-9	
1,3 Dioxolane	<20%	646-06-0	
Methanol	<2.5%	67-56-1	
Water	<1.5%	7732-18-5	

All concentrations are by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

SECTION 4 — FIRST AID MEASURES

Description of first aid measures:

General advice:

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

Move to fresh air. Get medical attention. Treat symptomatically.

Skin contact

Wash with soap and water. Get medical attention if symptoms persist. Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention. Wash contaminated clothing before reuse. Destroy or thoroughly clean contaminated shoes.

Eve contact

Immediately flush with plenty of water for at least 15 minutes. If easy to do so, remove contact lenses. Get medical attention.

Ingestion:

Call a physician or poison control center immediately. Only induce vomiting at the instructions of medical personnel. Never give anything by mouth to an unconscious person.

HLR Label & Adhesive Remover Page 3 of 9

Most important symptom and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (section 2) and/or section 11.

Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5—FIRE FIGHTING MEASURES

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Special hazards arising from the substance or mixture.

Carbon oxides

Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

Further information

Use water spray to cool unopened containers.

SECTION 6 — ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see Section 8.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Methods and material for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in Container for disposal according to local regulations (see section 13).

Reference to other sections

For disposal see section 13.

SECTION 7 — HANDLING & STORAGE

Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Use explosion-proof equipment. Keep away from sources of ignition – No smoking. Take measures to prevent the build up of electrostatic charge. For precautions see section 2.

Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers with are opened must be carefully resealed and kept upright to prevent leakage.

Specific end use(s)

Apart for the uses mentioned in section 1, no other specific uses are stipulated.

SECTION 8 — EXPOSURE CONTROL/PERSONAL PROTECTION

Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control	Basis
			parameters	

HLR Label & Adhesive Remover Page 4 of 9

Methyl acetate	79-20-9	TWA	200 ppm	US ACGIH Threshold Limit
				Values (TLV)
Methanol	67-56-1	TWA	200 ppm	US ACGIH Threshold Limit
				Values (TWA)
1,3-Dioxolane	646-06-0	TWA	20.000000 ppm	US ACGIH Threshold Limit
				Values (TLV)
	Remarks	Hematologic effects		

Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Eye/face protective equipment

Eye/face protection

Face shield and safety glasses. Use equipment for eye protection tested and approved under appropriate governmental standards such as NIOSH (us) or EN 166 (EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Body protection

Impervious clothing. Flame retardant antistatic protective clothing. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance: Clear, colourless, liquid

Odor: Solvent odor
Odor Threshold: No data available
pH No data available

Boiling point range: $55.8 - 75^{\circ}$

Flashpoint: -13 °C Tag Closed Cup (Lowest component)

Evaporation Rate: No data available Flammability (solid, gas_ No data available Upper/lower flammability limits: No data available

Vapour pressure: 228.3 mbar (20 C) Methyl Acetate

Relative density: N/A
Relative density: N/A
Water Solubility: soluble

Partition coefficient:

n-octanol/water N/A

HLR Label & Adhesive Remover Page 5 of 9

Auto-ignition temperature: 250°C (482°F) at 1,019.3 1.027.5 hPA (764.5 – 770.7 mmHg)

Decomposition temperature: No data available Viscosity: No data available Explosive properties: No data available Oxidizing properties: No data available

SECTION 10 — STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical Stability:

Stable under recommended storage condition Contains the following stabiliser(s): BHT (0.0075%)

Possibility of hazardous reactions:

Vapours may form explosive mixture with air.

Conditions to avoid:

Heat, flames and sparks

Incompatible materials:

Strong oxidizing agents.

Hazardous decomposition products

Other decomposition products – No data available. In the event of fire: section 5

SECTION 11 — TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Inhalation: May cause respiratory irritation. May cause drowsiness or dizziness.

Ingestion: None known. **Skin contact:** None known.

Eye contact: Causes serious eye damage.

Information on toxicological effects

Oral:

Methyl Acetate:

LD50 Oral – Rat): 6,482 mg/kg (highest dose tested)

Methanol:

LD-50 Oral – Rat: 5,600 mg/kg

1.3 Dioxolane:

LD50 Oral – Rat – male and female – 5,1200 mg/kg

(OECD Test Guideline 401)

Inhalation:

Methyl Acetate:

LC50 Inhalation – Rat – 4 h > 49 mg/l

Methanol:

LC50 Inhalation – Rat – 4 h: 64000 ppm

1,3 Dioxolane

LC50 Inhalation – Rat – male and female – 4 h – 68.4 mg/l

HLR Label & Adhesive Remover Page 6 of 9

(OECD Test Guideline 403)

Dermal:

Methyl Acetate:

LD50 Dermal – Rabbit > 2,000 mg/kg (highest does tested)

Methanol:

LD50 Dermal – Rabbit: 17,100 mg/kg

1,3 Dioxolane:

LD50 Dermal - Rat = 15,000 mg/kg

Skin corrosion/irritation

Skin – Rabbit

Result: No skin irritation

Serious eye damage/eye irritation

Eyes – Rabbit

Result: Irritating to eyes.

Respiratory or skin sensitisation

- Mouse

Result: Did not cause sensitisation on laboratory animals.

(OECD Test Guideline 429)

Germ cell mutagenicity

In vitro mammalian cell gene mutation test

Mouse lymphoma cells

Result: negative

Carcinogenicity

IARC: No component of this product present a levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity:

No data available

Specific target organ toxicity – single exposure:

No data available.

Specific target organ toxicity – repeated exposure:

No data available

Aspiration hazard

No data available

Additional Information:

Repeated dose toxicity (1,3 dioxolane)

Rat – male – Oral – NOAEL: 75 mg/kg – OECD Test Guideline 407

RTECS: JH6760000

SECTION 12 — ECOLOGICAL INFORMATION

Ecotoxicity:

Acute hazards to the aquatic environment:

HLR Label & Adhesive Remover Page 7 of 9

Fish:

Methyl Acetate:

LC-50 (Fathead Minnow, 96h): 320 – 399 mg/l

Methanol:

LC-50 (Bluegill Sunfish, 96 h): 15,400 mg/l

1,3 Dioxolane:

Semi-static test LC50 – Lepomis macrochirus - > 95.4 mg/l – 96 h

(OECD Test Guideline 203)

Aquatic Invertebrates:

1,3 Dioxolane:

Toxicity to daphnia and other aquatic invertebrates:

Immobilization EC50 – Daphnia magna (Water flea) - > 772 mg/l – 48 h

(OECD Test Guideline 202)

Toxicity to Aquatic Plants:

Methyl Acetate:

EC-50 (Selenastrum capricornutum, 72 h): > 120 mg/l

Methanol:

EC-50 Algae (Pseudokichneriella subcapitata), 96h >22,000 mg/l

1,3 Dioxolane:

EC50 Algae (Pseudokirchneriella subcapitata), 72h > 877 mg/l

Persistence and degradability:

Biodegradration:

Methyl Acetate: 70% (28 d) **Methanol:** 95% (20 d)

1,3 Dioxolane: 3.7% Aerobic (35 d) -According to the results of tests of biodegradability this product is not

readily biodegradable. OECD Test Guideline 301D)

Bioaccumulative potential:

No data available.

Mobility in soil: No data available.

Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not

conducted.

Other adverse effects: No data available.

SECTION 13 — DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of in accordance with all applicable local, state, and federal regulations

SECTION 14 — TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Flammable liquid, n.o.s.

Limited Quantity*.

DOT Hazard Class: 3 FLAMMABLE LIQUID

HLR Label & Adhesive Remover Page 8 of 9

UN/NA Number: UN1993 Packing Group: II

*Limited Quantity Exemption: This product, as packaged in 20 oz. containers, meets the exemption requirements of section 173.150 (49 CFR 173) as a limited quantity for ground shipments within the United States. Limited quantities require the limited quantity diamond mark on all outer cartons.

AIR TRANSPORT: We do NOT recommend this product to be shipped via air. It would need to be repacked by an authorized packing company and the DG would have to be completed by a licensed hazardous material shipping company.

SECTION 15 — REGULATORY INFORMATION

This material meets the EPA	[X] Yes	[] No	Acute (immediate) Health Hazard
'Hazard Categories' defined	[X] Yes	[] No	Chronic (delayed) Health Hazard
For SARA Title III Sections	[X] Yes	[] No	Fire Hazard
311/312 as indicated:	[] Yes	[X] No	Sudden Release of Pressure Hazard
	[] Yes	[X] No	Reactive Hazard

US EPCRA (SARA Title II) Section 313 – Toxic Chemical List: Methanol

CAS # Hazardous Components (Chemical Name) Other US EPA or State Lists

646-06-0 1,3-Dioxolane Massachusetts, Pennsylvania, New Jersey

California Prop. 65 Components: Methanol

This product can expose you to chemicals including methanol which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16 — OTHER INFORMATION

Full text of H-Statements referred to under section 2 and 3.

Eye Irrit. Eye irritation Flam. Liq. Flammable liquids

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation

HMIS Rating:

Health hazard: 2
Chronic health hazard: *
Flammability: 3
Physical hazard: 0

NFPA Rating:

Health hazard: 2
Fire hazard: 3
Reactivity hazard: 0

Revision Date: 08/09/2017

Prepared by: Albatross USA Inc. **Additional Information About** No data available

This Product:

Company Policy or Disclaimer: The information contained herein is presented in good faith and believed to

be accurate as of the effective date shown above. This information is

HLR Label & Adhesive Remover Page 9 of 9

furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.