

SDS Revision Date: 05/06/2015

# 1. Identification

1.1. Product identifier

Product Identity Cloud 9
Alternate Names Cloud 9

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Softener

Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name Gurtler Industries, Inc.

15475 South LaSalle St. South Holland, IL 60473 US

**Emergency** 

**24 hour Emergency Telephone No.** (708) 331-2550

Customer Service: Gurtler Industries, Inc. INFOTRAC - (800) 535-5053

# 2. Hazard(s) identification

## 2.1. Classification of the substance or mixture

No applicable GHS categories.

#### 2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.

No applicable GHS categories.

[Prevention]:

No GHS prevention statements

[Response]:

No GHS response statements

[Storage]:

No GHS storage statements

[Disposal]:

No GHS disposal statements



05/06/2015 **SDS Revision Date:** 

# 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Methyl Tallow Diethylenetriamine CAS Number: 0068410-69-5	1.0 - 10	Skin Irrit. 2;H315 Eye Dam. 2A;H319	[1]
Isopropyl Alcohol CAS Number: 0000067-63-0	1.0 - 10	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	[1][2]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. First aid measures

# 4.1. Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.

**Eyes** Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain

medical attention if irritation persists.

Skin Flush with cool water. Wash with soap and water. Obtain medical attention if irritation

persists.

Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk Ingestion

of aspiration. Never give anything by mouth if victim is unconscious, or is convulsing.

Obtain medical attention.

## 4.2. Most important symptoms and effects, both acute and delayed

## Overview

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatique, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

<sup>[1]</sup> Substance classified with a health or environmental hazard.

<sup>[2]</sup> Substance with a workplace exposure limit.

<sup>[3]</sup> PBT-substance or vPvB-substance.
\*The full texts of the phrases are shown in Section 16.



SDS Revision Date: 05/06/2015

# 5. Fire-fighting measures

## 5.1. Extinguishing media

Treat for surrounding material.

# 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Oxides of carbon, oxides of nitrogen, oxides of sulfur

#### 5.3. Advice for fire-fighters

Firefighters should wear full protective clothing including self-contained breathing apparatus.

ERG Guide No. ----

# 6. Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

#### 6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

## 6.3. Methods and material for containment and cleaning up

Personal precautions: Keep unnecessary personnel away. Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective space clothing. Keep people away from and upwind of spill/leak.

Environmental precautions: Do not discharge into lakes, streams, ponds or public waters.

Methods for containment: Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas.

Methods for cleaning up: Before attempting clean up, refer to hazard data given above. Small spills may be absorbed with non-reactive absorbent and placed in suitable, covered, labelled containers. Prevent large spills from entering sewers or waterways. Contact emergency services and supplier for advice. Never return spills to original containers for re-use.

# 7. Handling and storage

# 7.1. Precautions for safe handling

Use good industrial hygiene practices in handling this material. When using do not eat or drink.
Avoid contact with eyes.
Keep container tightly closed.
Use only with adequate ventilation.
Wash thoroughly after handling.



SDS Revision Date: 05/06/2015

Avoid breathing vapors or mists of this product.

See section 2 for further details. - [Prevention]:

# 7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Store in a closed container away from incompatible materials.

Incompatible materials: oxidizers

See section 2 for further details. - [Storage]:

## 7.3. Specific end use(s)

No data available.

# 8. Exposure controls and personal protection

## 8.1. Control parameters

## **Exposure**

CAS No.	Ingredient	Source	Value
0000067-63-0 Isopropyl Alcohol		OSHA	TWA 400 ppm (980 mg/m3)STEL 500 ppm
		ACGIH	TWA: 200 ppm STEL: 400 ppm Revised 2003,
		NIOSH	TWA 400 ppm (980 mg/m3) ST 500 ppm (1225 mg/m3)
		Supplier	No Established Limit
0068410-69-5	Methyl Tallow Diethylenetriamine	OSHA	No Established Limit
		ACGIH	No Established Limit
	NIOSH	No Established Limit	
		Supplier	No Established Limit

# Carcinogen Data

CAS No.	Ingredient	Source	Value
0000067-63-0	Isopropyl Alcohol	OSHA Select Carcinogen: No	
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0068410-69-5	Methyl Tallow Diethylenetriamine	e OSHA Select Carcinogen: No	
			Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

# 8.2. Exposure controls

**Respiratory** If workers are exposed to concentrations above the exposure limit they must use the

appropriate, certified respirators.

**Eyes** Protective safety glasses recommended

**Skin** Rubber gloves recommended.

**Engineering Controls** Provide adequate ventilation. Where reasonably practicable this should be achieved by the

use of local exhaust ventilation and good general extraction. If these are not sufficient to



SDS Revision Date: 05/06/2015

maintain concentrations of particulates and any vapor below occupational exposure limits

suitable respiratory protection must be worn.

using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

# 9. Physical and chemical properties

Appearance Opaque light blue Liquid

**Odor** Pleasant

Odor thresholdNot MeasuredpHNot MeasuredMelting point / freezing pointNot MeasuredInitial boiling point and boiling range> 212 F/100 C

Flash Point > 199.9 F/93.3 C (TCC)

Evaporation rate (Ether = 1) Not Measured
Flammability (solid, gas) Not Applicable

Upper/lower flammability or explosive limits Lower Explosive Limit: Not Measured

**Upper Explosive Limit:** Not Measured

Vapor pressure (Pa)Not MeasuredVapor DensityNot Measured

Specific Gravity

Solubility in Water

Partition coefficient n-octanol/water (Log Kow)

Auto-ignition temperature

Decomposition temperature

Viscosity (cSt)

0.995

Not Measured

Not Measured

Not Measured

Viscosity (cSt)

<100 cPs

9.2. Other information

No other relevant information.

# 10. Stability and reactivity

#### 10.1. Reactivity

Hazardous Polymerization will not occur.

# 10.2. Chemical stability

Stable under normal circumstances.

#### 10.3. Possibility of hazardous reactions

Strong Oxidizers

#### 10.4. Conditions to avoid

Do not mix with other chemicals.



SDS Revision Date: 05/06/2015

10.5. Incompatible materials

oxidizers

10.6. Hazardous decomposition products

Oxides of carbon, oxides of nitrogen, oxides of sulfur

# 11. Toxicological information

## **Acute toxicity**

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Methyl Tallow Diethylenetriamine - (68410-69-5)	No data available	No data available	No data available	No data available	No data available
Isopropyl Alcohol - (67-63-0)	4,710.00, Rat - Category: 5	12,800.00, Rat - Category: NA	72.60, Rat - Category: NA	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)		Not Applicable
Skin corrosion/irritation		Not Applicable
Serious eye damage/irritation		Not Applicable
Respiratory sensitization		Not Applicable
Skin sensitization		Not Applicable
Germ cell mutagenicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive toxicity		Not Applicable
STOT-single exposure		Not Applicable
STOT-repeated exposure		Not Applicable



SDS Revision Date: 05/06/2015

Aspiration hazard	 Not Applicable

# 12. Ecological information

# 12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

# **Aquatic Ecotoxicity**

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Methyl Tallow Diethylenetriamine - (68410-69-5)	Not Available	Not Available	Not Available
Isopropyl Alcohol - (67-63-0)	1,400.00, Lepomis macrochirus	100.00, Daphnia magna	100.00 (72 hr), Scenedesmus subspicatus

# 12.2. Persistence and degradability

There is no data available on the preparation itself.

# 12.3. Bioaccumulative potential

Not Measured

## 12.4. Mobility in soil

No data available.

# 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

# 12.6. Other adverse effects

No data available.

# 13. Disposal considerations

## 13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

# 14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	Not Applicable	Not Regulated	Not Regulated
14.2. UN proper shipping name	Not Regulated	Not Regulated	Not Regulated
14.3. Transport hazard class(es)	<b>DOT Hazard Class:</b> Not Applicable	IMDG: Not Applicable Sub Class: Not Applicable	Air Class: Not Applicable
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable



SDS Revision Date: 05/06/2015

14.5. Environmental hazards

IMDG Marine Pollutant: No

14.6. Special precautions for user

No further information

# 15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected

regulations are represented.

Toxic Substance Control Act (TSCA) All components of this material are either listed or exempt from listing on the TSCA

Inventory.

WHMIS Classification B3

US EPA Tier II Hazards Fire: No

Sudden Release of Pressure: No

Reactive: No

Immediate (Acute): No Delayed (Chronic): No

#### EPCRA 311/312 Chemicals and RQs:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### **EPCRA 302 Extremely Hazardous:**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### **EPCRA 313 Toxic Chemicals:**

Isopropyl Alcohol

#### Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

## Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

## **Proposition 65 - Female Repro Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

## **Proposition 65 - Male Repro Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### **New Jersey RTK Substances (>1%):**

Isopropyl Alcohol

### Pennsylvania RTK Substances (>1%):

Isopropyl Alcohol



SDS Revision Date: 05/06/2015

# 16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

**End of Document**