

Page 1/11

Safety Data Sheet acc. to OSHA HCS

Printing date 11/04/2019 Reviewed on 11/04/2019

1 Identification

- · Product identifier
- · Trade name: Mega Power
- · Application of the substance / the mixture

Laundry Detergent

- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SEITZ GmbH

Gutenbergstrasse 1 - 3

65830 Kriftel / Germany

Tel. + 49(0) 6192-9948-0

Fax + 49(0) 6192-9948-99

order@seitz24.com

www.seitz24.com

· Information department:

CHEM-TEL Inc.

1305 North Florida Ave

Tampa Florida 33602

· Emergency telephone number: 1-800-255-3924 (24-hour Service)

2 Hazard(s) identification

· Classification of the substance or mixture

Acute Tox. 4 H302 Harmful if swallowed.

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS05 GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

sodium metasilicate, pentahydrate

isotridecanol, ethoxylated

isotridecanol, ethoxylated

Hazard statements

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation.

(Contd. on page 2)



Page 2/11

Safety Data Sheet acc. to OSHA HCS

Printing date 11/04/2019 Reviewed on 11/04/2019

Trade name: Mega Power

(Contd. of page 1)

· Precautionary statements

P260 Do not breathe dust.

P280 Wear protective gloves / eye protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· CAS-No. Components:			
CAS: 10213-79-3	sodium metasilicate, pentahydrate	15 – 40%	
CAS: 497-19-8	sodium carbonate	15 – 40%	
CAS: 7757-82-6	sodium sulphate	1 – 5%	
CAS: 69011-36-5	isotridecanol, ethoxylated	0.1 – 1%	
CAS: 69011-36-5	isotridecanol, ethoxylated	0.1 – 1%	

· Additional information For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- · Description of first aid measures
- · General information

Remove casualties from exposure.

Keep unprotected persons away.

Immediately remove any clothing soiled by the product.

- · After inhalation Supply fresh air; consult doctor in case of complaints.
- · After skin contact

Immediately rinse with water.

Seek medical treatment.

· After eye contact

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

- · Information for doctor
- · Most important symptoms and effects, both acute and delayed

Causes severe skin burns and eye damage.

May cause respiratory irritation.

(Contd. on page 3)



Page 3/11

Safety Data Sheet acc. to OSHA HCS

Printing date 11/04/2019 Reviewed on 11/04/2019

Trade name: Mega Power

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed Symptomatic treatment

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents No further relevant information available.
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · Advice for firefighters
- · Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Avoid contact with eyes and skin.

Avoid formation of dust.

- · Environmental precautions: Do not allow product to reach sewage system or any water course.
- · Methods and material for containment and cleaning up:

Pick up mechanically.

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling
- · Precautions for safe handling

Keep away from heat and direct sunlight.

Prevent formation of dust.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Avoid contact with eyes and skin.

· Information about protection against explosions and fires: No special measures required.

(Contd. on page 4)



Page 4/11

Safety Data Sheet acc. to OSHA HCS

Printing date 11/04/2019 Reviewed on 11/04/2019

Trade name: Mega Power

(Contd. of page 3)

- · Conditions for safe storage, including any incompatibilities
- Storage
- Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Unsuitable material for receptacle: aluminium.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Protect from heat and direct sunlight.

Store in cool, dry conditions in well sealed receptacles.

Protect from humidity and water. Time of storage: max. 36 month

· Specific end use(s) Laundry

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

CAS: 7757-82-6 sodium sulphate

TLV Short-term value: NIC-0.2 mg/m³ thoracic fraction of aerosol

- · Regulatory information TLV: Guide to Occupational Exposure Values (ACGIH)
- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment
- · General protective and hygienic measures

The usual precautionary measures for handling chemicals should be followed.

Do not eat, drink, smoke or sniff while working.

Vacuum clean contaminated clothing. Do not blow or brush off contamination.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not inhale dust / smoke / mist.

- · Breathing equipment: By formation of dust: dust mask
- · Protection of hands:

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)



Page 5/11

Safety Data Sheet acc. to OSHA HCS

Printing date 11/04/2019 Reviewed on 11/04/2019

Trade name: Mega Power

(Contd. of page 4)

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection: Tightly sealed goggles.
 Body protection: Protective work clothing.

Physical and chemical propert	ios	
 Information on basic physical and ch General Information 	nemical properties	
· Appearance:		
Form:	Powder	
Color:	White	
· Odor:	Product specific	
· pH-value (100 g/l) at 40 °C (104 °F):	~ 12.6	
· Change in condition		
Melting point/Melting range:	undetermined	
Boiling point/Boiling range:	not applicable	
· Flash point:	Not applicable	
· Flammability (solid, gaseous)	No further relevant information available.	
· Ignition temperature:	No further relevant information available.	
Decomposition temperature:	No further relevant information available.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion ha	zard.
· Explosion limits:		
Lower:	No further relevant information available.	
Upper:	No further relevant information available.	
Oxidizing properties	No further relevant information available.	
· Vapor pressure:	No further relevant information available.	
· Density:		
Bulk density at 20 °C (68 °F):	~ 910 kg/m³	
Relative density	No further relevant information available.	
Vapor density	No further relevant information available.	
Evaporation rate	No further relevant information available.	
· Solubility in / Miscibility with		
Water:	Easily soluble	
· Partition coefficient (n-octanol/water): No further relevant information available.	
· Viscosity:		
dynamic:	No further relevant information available.	
kinematic:	No further relevant information available.	



Page 6/11

Safety Data Sheet acc. to OSHA HCS

Reviewed on 11/04/2019 Printing date 11/04/2019

Trade name: Mega Power

(Contd. of page 5)

· Other information

No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability

Stable under normal ambient conditions.

No decomposition if used and stored according to specifications.

Possibility of hazardous reactions

Reacts with acids

Corrodes aluminium

- · Conditions to avoid No further relevant information available.
- · Incompatible materials:

Acids

Certain metals

· Hazardous decomposition products: No dangerous decomposition products known

11 Toxicological information

LD50

- · Information on toxicological effects
- · Acute toxicity

 LD/LC50 values that are relevant for class
--

ATE (Acute Toxicity Estimate) Oral LD50 > 1,766 - 2,149 mg/kg (rat) LD50 > 23.686 mg/kgDermal Inhalative I C50 (4h) > 2.609 mg/l (rat)

	2000 (111)	2,009 mg/i (rat)	
CAS: 1021	13-79-3 soc	dium metasilicate, pentahydrate	
Oral	LD50	1,152 – 1,349 mg/kg (rat)	
Dermal	LD50	> 5,000 mg/kg (rat)	
Inhalative	LC50	> 2,060 mg/m³ (rat)	
CAS: 497-	CAS: 497-19-8 sodium carbonate		
Oral	LD50	2,800 mg/kg (rat)	
CAS: 7757	CAS: 7757-82-6 sodium sulphate		
Oral	LD50	5,898 mg/kg (rat)	
CAS: 6901	11-36-5 iso	tridecanol, ethoxylated	
Oral	LD50	> 300 – 2,000 mg/kg (rat)	
Dermal	LD50	> 2,000 mg/kg (rat)	
CAS: 6901	CAS: 69011-36-5 isotridecanol, ethoxylated		
Oral	LD50	> 300 – 2,000 mg/kg (rat)	
Oral Dermal Inhalative CAS: 497- Oral CAS: 7757 Oral CAS: 6907 Oral Dermal CAS: 6907	LD50 LD50 LC50 -19-8 sodiu LD50 7-82-6 sodi LD50 11-36-5 iso LD50 LD50	1,152 – 1,349 mg/kg (rat) > 5,000 mg/kg (rat) > 2,060 mg/m³ (rat) m carbonate 2,800 mg/kg (rat) ium sulphate 5,898 mg/kg (rat) tridecanol, ethoxylated > 300 – 2,000 mg/kg (rat) > 2,000 mg/kg (rat) tridecanol, ethoxylated	

- > 2,000 mg/kg (rabbit) Skin corrosion/irritation Causes severe skin burns and eye damage.
- · Serious eye damage/irritation Causes serious eye damage.

(Contd. on page 7)



Page 7/11

Safety Data Sheet acc. to OSHA HCS

Printing date 11/04/2019 Reviewed on 11/04/2019

Trade name: Mega Power

(Contd. of page 6)

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- Specific target organ toxicity single exposure May cause respiratory irritation. Specific target organ toxicity repeated exposure

Based on available data, the classification criteria are not met.

· Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological information

· Toxicit	ty
· Aquati	c toxicity:
CAS: 1	10213-79-3 sodium metasilicate, pentahydrate
EC50	1,700 mg/l (Aquatic invertebrates) (48 h; Daphnia magna)
LC50	210 mg/l (Fish) (96 h; Brachydanio rerio)
CAS: 4	197-19-8 sodium carbonate
LC50	300 mg/l (Fish) (96 h; Lepomis macrochirus)
	200 mg/l (Aquatic invertebrates) (48 h; Ceriodaphnia sp.)
CAS: 6	9011-36-5 isotridecanol, ethoxylated
EC50	> 1 mg/l (Aquatic plants, algae) (72 h; Desmodesmus subspicatus; OECD 201)
	> 1 mg/l (Aquatic invertebrates) (48 h; Daphnia magna; OECD 202)
LC50	> 1 mg/l (Fish) (96 h; Cyprinus carpio; OECD 203)
CAS: 6	9011-36-5 isotridecanol, ethoxylated
EC50	> 1 – 10 mg/l (Aquatic invertebrates) (48 h; Daphnia magna; OECD 202)
LC50	> 1 – 10 mg/l (Fish) (96 h; Cyprinus carpio; OECD 203)
EC10	> 1 – 10 mg/l (Aquatic plants, algae) (72 h; Desmodesmus subspicatus; OECD 201)
NOEC	2.5 mg/l (Aquatic invertebrates) (21 d; Daphnia magna; OECD 211)

- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

(Contd. on page 8)



Page 8/11

Safety Data Sheet acc. to OSHA HCS

Printing date 11/04/2019 Reviewed on 11/04/2019

Trade name: Mega Power

(Contd. of page 7)

- Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Contaminated adsorbent, soil, water must be disposed of in a permitted hazardous waste management facility. Recovered products may be reused, reprocessed or incinerated or must be treated in a permitted hazardous waste management facility. It is your duty to dispose of the chemical materials and/or their containers in accordance with the Clean Air Act, The Clean Water Act, RCRA, as well as applicable Federal, State, and local Regulations regarding disposal.

UN-Number DOT, ADR, IMDG, IATA	UN3262
UN proper shipping name DOT	Corrosive solid, basic, inorganic, n.o.s. (Disodium trioxosilicate)
ADR	3262 CORROSIVE SOLID, BASIC, INORGANIC, N.O.S. (DISODIUM TRIOXOSILICATE)
IMDG, IATA	CORROSIVE SOLID, BASIC, INORGANIC, N.O.S (DISODIUM TRIOXOSILICATE)
Transport hazard class(es)	
DOT	
CORROSVE 8	
Class	8 Corrosive substances

(Contd. on page 9)



Page 9/11

Safety Data Sheet acc. to OSHA HCS

Printing date 11/04/2019 Reviewed on 11/04/2019

Trade name: Mega Power

	(Contd. of page
Label	8
ADR	
Class	8 (C6) Corrosive substances
Label	8
IMDG, IATA	
Class	8 Corrosive substances
· Label	8
Packing group DOT, ADR, IMDG, IATA	III
Environmental hazards:	Not applicable.
Special precautions for user Danger code (Kemler): EMS Number: Segregation groups Stowage Category	Warning: Corrosive substances 80 F-A,S-B Alkalis A
Segregation Code	SG35 Stow "separated from" SGG1-acids
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.
Transport/Additional information:	
· DOT · Quantity limitations	On passenger aircraft/rail: 25 kg On cargo aircraft only: 100 kg
· ADR · Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 1000 g
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5 kg Code: E1 Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 1000 g



Page 10/11

Safety Data Sheet acc. to OSHA HCS

Printing date 11/04/2019 Reviewed on 11/04/2019

Trade name: Mega Power

(Contd. of page 9)

· UN "Model Regulation":

UN 3262 CORROSIVE SOLID, BASIC, INORGANIC, N.O.S. (DISODIUM TRIOXOSILICATE), 8, III

15 Regulatory information

Sara

Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (specific toxic chemical listings):

CAS: 7758-29-4 pentasodium triphosphate

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· New Jersey Right-to-Know List:

None of the ingredients is listed.

New Jersey Special Hazardous Substance List:

None of the ingredients is listed.

· Pennsylvania Right-to-Know List:

CAS: 7758-29-4 pentasodium triphosphate

CAS: 7757-82-6 sodium sulphate

· Pennsylvania Special Hazardous Substance List:

CAS: 7758-29-4 pentasodium triphosphate E
CAS: 7757-82-6 sodium sulphate E

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

(Contd. on page 11)



Page 11/11

Safety Data Sheet acc. to OSHA HCS

Printing date 11/04/2019 Reviewed on 11/04/2019

Trade name: Mega Power

(Contd. of page 10)

- National regulations
- · Other regulations, limitations and prohibitive regulations
- · Please note:

The information herein is presented in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied is given. Regulatory requirements are subject to change and may differ from one location to another. It is the buyers responsibility to ensure that their activities comply with Federal, State or provincial and local laws. The following specific information is made for the purpose of complying with numerous laws and regulations.

Other information: The product has been designed for professional use only.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Date of preparation / last revision 11/04/2019 / 4.00
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Eye Dam. 1: Serious eye damage/eye irritation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

* Data compared to the previous version altered.